

MATERIAL SAFETY DATA SHEET**CYANOACRYLATE ADHESIVE (40 cps)****1. HAZARDOUS INGREDIENTS:**

	CAS NO.	%	NTP	IARC	OSHA
Ethyl Cyanoacrylate	7085-85-0	95-100	NO	NO	NO
Hydroquinone	123-31-9	0.1-0.5	NO	N/A	NO
Poly (Methyl) Methacrylate	9011-14-7	3-5	NO	N/A	NO

2. PHYSICAL DATA:

Boiling Point	: More than 300 °F	Specific Gravity	: 1.06
Vapor Pressure	: Less than 0.2mm @ 75 °F	Volatile Organic Comp.	: 98.8 %
Vapor Density	: Approximately 3	Evaporation Rate	: N/A
Solubility in Water	: Polymerized by water	Odor	: Sharp, irritating
Appearance	: Clear Liquid		

3. FIRE AND EXPLOSION HAZARD DATA:

Flash Point	: 185 °F (method used – T.C.C.)
Extinguishing Media	: Carbon Dioxide, Dry Chemical, Foam
Unusual Fire & Explosion Hazards	: Possible exothermic reaction leading to substrate ignition and fume generation.
Flammable Limits	: LEL : N/A UEL : N/A
Special Fire Fighting Procedures	: Self contained breathing apparatus.

4. HEALTH HAZARD DATA:

Threshold Limit Value	: No criteria for measurement. Not yet established. Estimated 2ppm.
Effects of Overexposure	: Vapor is irritating to eyes and mucous membranes above TLV. Prolonged and repeated overexposure to vapors may produce allergic reactions with asthma-like symptoms in sensitive individuals.
Emergency and First Aid Procedures	: Skin : immerse bonded surface in warm soapy water. Peel or roll surface apart with aid of blunt edge. Do not pull apart with direct opposing action. Eye : flush with warm water and apply cause patch. Mouth : apply warm water to mouth. Peel or roll lips apart. Burns : should be treated normally after the lump of cyanoacrylate is released from the tissue. Inhalation : remove to fresh air.

PAGE 2
CYANOACRYLATE ADHESIVE (40 cps)

5. REACTIVITY DATA:

Stability	: Stable (under normal conditions)
Conditions to Avoid	: Amines, Base Materials
Hazardous Decomposition Products	: None
Hazardous Polymerization	: May occur (Exothermic)
Incompatibility (materials to avoid)	: Polymerized by contact with water, alcohols, amines, alkalies

6. SPILL OR LEAK PROCEDURES:

Steps to be taken in case material is released or spilled:

Flood with water to polymerize. Soak up with an inert absorbent.

Waste Disposal Method:

Polymerize as above. Incinerate in accordance with EPA and local regulations.

7. SPECIAL PROTECTION INFORMATION:

Respiratory Protection (type)	: None needed for normal use.
Ventilation	: Positive down-draft exhaust ventilation should be provided to maintain Vapor concentration below TLV.
Protective Gloves	: Polyethylene gloves, do not use cotton gloves.
Eye Protection	: Safety glasses or goggles.
Other Protective Equipment	: Polyethylene/Polypropylene coats or aprons (not rubber or cotton).

8. SPECIAL PRECAUTIONS:

Precautions to be taken in handling and storage:

Store at or below 75 °F to maximize shelf life.

Other Precautions:

Avoid contact with skin and eyes. Avoid breathing vapor.

Disclaimer: Information contained herein is produced in good faith and is believed to be reliable but is intended to serve as a guide only. Uni-Continental Distributors c.c. and it's agents cannot assume liability for loss, accident or consequence from the use of such information. The user should satisfy themselves as to the products suitability for their requirements and adopt such precautions as is required for the protection of personnel and property in the handling and usage of Uni-Continental Distributors c.c. materials.